PORTABLE LED HEADLIGHT SYSTEM



SEE BETTER
SEE FARTHER
SEE WHY

SINCE 1977
ENHANCING
YOUR VISION



DAYMARK TM SURGICAL

HIGH-INTENSITY, PORTABLE LED SURGICAL HEADLIGHT WITH ADJUSTABLE SPOT, POWERED BY A 4-CELL BATTERY

- Illumination Range: ~60,000 LUX at 16" (40 cm) to ~260,000 LUX at 10" (25 cm)
- Adjustable Spot Diameter: 1"-4"(2.5 10.16 cm) at a working distance of 16" (40 cm)
- Color Rendering Index: 78 CRI
- Color Temperature: 5,000 K
- Intensity Settings: 5 Levels
- 4-Cell Battery
- Battery Duration at Full Intensity: 5 hours
- Battery Expected Life Span: > 300 Charges
- LED Expected Life Span: > 10,000 hours
- Optic Weight: 5 oz (141 g)Battery Weight: 8 oz (226 g)





DAYMARK PORTABLE LED HEADLIGHT SYSTEM INCLUDES:

- Daymark Surgical Headlight on Fiji Headband
- Two 4-Cell Batteries
- Charging Cradle, Power Supply
- Holster, Linkage Kit, and Carrying Case

DAYMARK PORTABLE LED HEADLIGHT SYSTEM PRODUCT CODES:

BFW 9070 Daymark Headlight System with Fiji Headband with Two 4-Cell Batteries

BFW 9076 Daymark Holster

BFW 9015 Daymark 4-Cell Battery
BFW 9022ACC Daymark Mini Battery Charger

EXCELLENT FOR USE IN THE FOLLOWING DEPARTMENTS

HOSPITAL

ENT
GENERAL SURGERY
CARDIOSURGERY
NEUROSURGERY
ORTHOPEDIC SURGERY
PEDIATRIC SURGERY
SPINE SURGERY
THORACIC SURGERY
TRANSPLANT SURGERY
VASCULAR SURGERY

SURGERY CENTER

ORTHOPEDIC SURGERY PLASTIC SURGERY

OFFICE

DENTAL EXAM

ORAL/MAXILLOFACIAL



BFWinc.com

800-717-4673 | +1-502-899-1808

445 BAXTER AVENUE | SUITE 175

LOUISVILLE, KY 40204 USA





DAYMARK TESTED AND CERTIFIED TO: IEC 60601-1 Edition 3, IEC 60601-1-2 Edition 4 ANSI/AAMI ES60601-1 (2005 + C1:09 + A2:10), CAN/CSA-C22.2 NO 60601-1 (2008), CE

ENGINEERED AND ASSEMBLED IN THE U.S.A. © 2020 BFW, Inc.
ALL TECHNICAL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE